



DSC-210

RECESSED ACCESS DOOR

For Acoustical Tile



GENERAL SCOPE:

Access Doors shall be Karp Type DSC-210 as manufactured by Karp Associates, Inc.

CONSTRUCTION:

1. Frame shall be 14 gauge steel and door shall be 16 gauge steel.
2. Door shall be recessed 1"
3. Hinge shall be concealed pivoting rod type.
4. Locks shall be flush and screwdriver operated with stainless steel cam and studs, or shall be key operated cylinder lock with automatic dust shutter.
5. Finish shall be prime coat of rust inhibitive electrostatic powder, baked grey enamel.

PROJECT DATA

Date:

Project Name:

Architect:

Contractor:

Agent/Customer Name:

Tagging Instructions:

Special Instructions:

PROJECT SCHEDULE

Qty.	H	W	No. Of Latches	Finish	Remarks

STANDARD SIZES

Door Size H & W	Wall/Ceiling Opening (Inches)	Number Of Latches	Shipping Wt. (lbs.)
12x12	12 1/8 x 12 1/8	1	6.7
18x18	18 1/8 x 18 1/8	2	12.4
24x12	24 1/8 x 12 1/8	2	10.6
24x24	24 1/8 x 24 1/8	2	19.2
36x24	36 1/8 x 24 1/8	2	32.0

