



DSC-214M

UNIVERSAL FLUSH ACCESS DOOR

Prime Coated Steel or Stainless Steel



GENERAL SCOPE:

Access Doors shall be Karp Type DSC-214M as manufactured by Karp Associates, Inc.

CONSTRUCTION:

1. Frame shall be 16 gauge steel and door shall be 14 gauge steel.
2. Flange of frame shall be one-piece construction. 3/4" wide.
3. Hinge shall be concealed continuous piano hinge. Where space conditions prevent door from swinging open, removable door lift or hinges or screws can be provided.
4. Locks shall be flush and screwdriver operated with stainless steel cam and studs, or shall be key operated cylinder lock with automatic dust shutter.
5. Masonry anchor straps can be included on frames if specified
6. Finish shall be prime coat of rust inhibitive electrostatic powder, baked grey enamel.
7. Stainless steel shall have No.4 stain polish finish.

STANDARD SIZES			
Door Size H & W	Wall/Ceiling Opening (Inches)	Number Of Latches	Shipping Wt. (lbs.)
6x6	6 3/8 x 6 3/8	1	2.1
8x8*	8 3/8 x 8 3/8	1	3.1
10x10*	10 3/8 x 10 3/8	1	4.3
12x8	12 3/8 x 8 3/8	1	4.6
12x12*	12 3/8 x 12 3/8	1	6.3
14x14	14 3/8 x 14 3/8	2	8.1
16x12	16 3/8 x 12 3/8	2	7.8
16x16*	16 3/8 x 16 3/8	2	9.9
18x12	18 3/8 x 12 3/8	2	8.9
18x18*	18 3/8 x 18 3/8	2	12.2
20x16	20 3/8 x 16 3/8	2	11.8
22x22	22 3/8 x 22 3/8	4	16.3
24x12	24 3/8 x 12 3/8	2	10.6
24x18	24 3/8 x 18 3/8	2	14.5
24x20	24 3/8 x 20 3/8	2	16.5
24x24*	24 3/8 x 24 3/8	5	18.7
30x20	30 3/8 x 20 3/8	5	20.1
30x22	30 3/8 x 22 3/8	5	21.7
30x24	30 3/8 x 24 3/8	5	23.6
30x30	30 3/8 x 30 3/8	5	27.8
36x32	36 3/8 x 32 3/8	5	25.6
36x24	36 3/8 x 24 3/8	5	28.2
36x36	36 3/8 x 36 3/8	5	36.8
48x24	48 3/8 x 24 3/8	6	34.4

*Stock Sizes Available In Stainless Steel

PROJECT DATA					
Date:					
Project Name:					
Architect:					
Contractor:					
Agent/Customer Name:					
Tagging Instructions:					
Special Instructions:					
PROJECT SCHEDULE					
Qty.	H	W	No. Of Latches	Finish	Remarks

