



## KDW

### FLUSH DRYWALL ACCESS DOOR

For Wall and Ceilings



#### GENERAL SCOPE:

Access Doors shall be Karp Type KDW as manufactured by Karp Associates, Inc.

#### CONSTRUCTION:

1. Frame shall be 16 gauge steel and door shall be 14 gauge steel.
2. Trim shall be galvanized steel drywall bead.
3. Hinge shall be concealed, continuous piano hinge.
4. Locks shall be flush and screwdriver operated with stainless steel cam and studs, or shall be key operated cylinder lock with automatic dust shutter.
5. Finish shall be prime coat of rust inhibitive electrostatic powder, baked grey enamel.

#### PROJECT DATA

Date:
Project Name:
Architect:
Contractor:
Agent/Customer Name:
Tagging Instructions:
Special Instructions:

#### PROJECT SCHEDULE

Qty.	H	W	No. Of Latches	Finish	Remarks

#### STANDARD SIZES

Door Size H & W	Wall/Ceiling Opening (Inches)	Number Of Latches	Shipping Wt. (lbs.)
6x6	6 <sup>3/8</sup> x 6 <sup>3/8</sup>	1	1.8
8x8	8 <sup>3/8</sup> x 8 <sup>3/8</sup>	1	2.4
10x10	10 <sup>3/8</sup> x 10 <sup>3/8</sup>	1	3.3
12x12	12 <sup>3/8</sup> x 12 <sup>3/8</sup>	1	5.8
14x14	14 <sup>3/8</sup> x 14 <sup>3/8</sup>	2	6.5
16x16	16 <sup>3/8</sup> x 16 <sup>3/8</sup>	2	8.8
18x18	18 <sup>3/8</sup> x 18 <sup>3/8</sup>	2	11.1
22x22	22 <sup>3/8</sup> x 22 <sup>3/8</sup>	4	15.3
24x24	24 <sup>3/8</sup> x 24 <sup>3/8</sup>	5	17.2
36x24	36 <sup>3/8</sup> x 24 <sup>3/8</sup>	5	25.9

