



KFD

FLOOR ACCESS DOOR Hinged (Watertight)



GENERAL SCOPE:

Access Doors shall be Karp Type KFD as manufactured by Karp Associates, Inc.

CONSTRUCTION:

1. Frame shall be aluminum extrusion with integral anchor flanges (watertight frame includes drain channel and neoprene gasket).
2. Hinges and all hardware shall be stainless steel.
3. Door leaf shall be diamond tread plate to withstand a live load of 300 lbs./sq.ft. or H2O loading without impact. Operation shall be assisted with stainless steel compression springs (optional). A hold open arm shall automatically lock the door in a 90° position.
4. Door can be equipped with a staple, staple and hasp, recessed hasp, stainless steel snap, brass pentahead or keyed cylinder lock.
5. Finish shall be a mill finish, with bituminous coating applied to the exterior of frame.

PROJECT DATA					
Date:					
Project Name:					
Architect:					
Contractor:					
Agent/Customer Name:					
Tagging Instructions:					
Special Instructions:					
PROJECT SCHEDULE					
Qty.	H	W	No. Of Latches	Finish	Remarks

STANDARD SIZES		
Door Size H & W	Shipping Wt. (lbs.)	
	KFD-SD	KFD-HD
24x24	50.0	71.0
30x24	56.0	81.0
30x30	63.0	93.0
36x24	62.0	91.0
36x30	70.0	105.0
36x36	78.0	118.0
48x36	97.0	147.0
48x48	118.0	181.0
72x48	158.0	248.0

