



## PF

### PRESS-FIT ACCESS DOOR Coated Steel or Stainless Steel



#### GENERAL SCOPE:

Access Doors shall be Karp Type Press-Fit as manufactured by Karp Associates, Inc.

#### CONSTRUCTION:

1. Trim, return, and door stop shall be one-piece construction. On doors 18"x18" and larger, the door shall be 20 gage steel. On doors smaller than 18"x18", the door shall be 22 gage steel.
2. Flange of frame shall be 1/2" wide and beveled.
3. Hinge shall be concealed, continuous piano hinge.
4. Locks shall be flush screwdriver operated with stainless steel cams and studs, or key operated cylinder lock with automatic dust shutter.
5. Return shall have bendable tabs for easy installation into drywall.
6. Finish shall be prime coat of rust inhibitive electrostatic powder, baked grey enamel.

PROJECT DATA					
Date:					
Project Name:					
Architect:					
Contractor:					
Agent/Customer Name:					
Tagging Instructions:					
Special Instructions:					
PROJECT SCHEDULE					
Qty.	H	W	No. Of Latches	Finish	Remarks

STANDARD SIZES			
Door Size H & W	Wall/Ceiling Opening (In.)	Number Of Stud Latches	Shipping Wt. (lbs.)
8x8	7 <sup>13/16</sup> x 7 <sup>13/16</sup>	1	1.5
12x12	11 <sup>13/16</sup> x 11 <sup>13/16</sup>	1	2.5
14x14	13 <sup>13/16</sup> x 13 <sup>13/16</sup>	1	3.0
18x18	17 <sup>13/16</sup> x 17 <sup>13/16</sup>	2	4.6
24x24	23 <sup>13/16</sup> x 23 <sup>13/16</sup>	2	7.4

